



AMX5C M12 \_\_\_Stand-alone safety switch without safety module


# CODED, NON-CONTACT, ELECTRO-MECHANI-CALSAFETY SWITCH TO CONTROL MACHINE GUARDS


- →Incorporated automatic self-monitoring
- → Switching distance/hysteresis: 11 mm/3 mm
- →2NO 2A/48V & 1NC 250mA/24V
- →LED indication of switch condition
- →Polycarbonate housing
- → Power supply: 24 V ac/dc -15% /+10% 50 /60 Hz
- → Protection class IP67/Temperature -20°C to +60°C
- → Auxiliary output : NC, PNP/250 mA
- → With incorporated M12-connector

## SAFETY CATEGORY

AMX5C M12: category 3 according to EN954-1 AMX5C M12: category 4\* with safety module. \*Regardless of number of switches in series

#### DIAGRAM






Complied with **UL/CSA** EN 60947-5-1

# Category 3 according to EN954-1

# **DIMENSIONS**



### PIN DETAILS

Male input connector:

- 1 white NO1
- 2 brown 24V
- 3 green AUX PNP NS
- 4 yellow NO2
- 5 grey NO1
- 6 pink NO2
- 7 blue 0V
- 8 red nc

(nc: not connected)

# INM



## **APPLICATION**

It remains the advantage of AMX5 and simplifies the wiring in series.

Our switches are equipped with a 2A fuse to guarantee the electrical protection.